



## FACTORY PRE-INSTALLED SILICONE CABLES SPECIFICATIONS



	DOUBLE-ENDED	DOUBLE-ENDED	DOUBLE-ENDED	DOUBLE-ENDED	SPLITTER
	Double-Ended Cable	Double-Ended Cable	Double-Ended Cable	Double-Ended Cable	Splitter Cable
Male Connector	straight	straight	angled	angled	straight
Female Connector	straight	angled	straight	angled	straight
Cable Material	TPE	TPE	TPE	TPE	TPE
Protective Cable Jacket	Silicone Tube	Silicone Tube	Silicone Tube	Silicone Tube	Silicone Tube
Locking Nuts	PTFE Coated	PTFE Coated	PTFE Coated	PTFE Coated	PTFE Coated
LED on Female End	Power and Output	Power and Output	Power and Output	Power and Output	
M12, 4-pin - 0.6m PNP	R-MS4TZ-T070.6+ R-FS4/3TP-T070.6-S	R-MS4TZ-T070.6+ R-FA4/3TP-T070.6-S	R-MA4TZ-T070.6+ R-FS4/3TP-T070.6-S	R-MA4TZ-T070.6+ R-FA4/3TP-T070.6-S	
M12, 4-pin - 0.6m no LED	R-MS4TZ-T070.6+ R-FS4TZ-T070.6-S	R-MS4TZ-T070.6+ R-FA4/3TZ-T070.6-S	R-MA4TZ-T070.6+ R-FS4/3TZ-T070.6-S	R-MA4TZ-T070.6+ R-FA4/3TZ-T070.6-S	U2-R4R-FS4KZ-T070.6-S
M12, 4-pin- 2.0m PNP	R-MS4TZ-T072+ R-FS4/3TP-T072-S	R-MS4TZ-T072+ R-FA4/3TP-T072-S	R-MA4TZ-T072+ R-FS4/3TP-T072-S	R-MA4TZ-T072+ R-FA4/3TP-T072-S	
M12, 4-pin - 2.0m no LED	R-MS4TZ-T072+ R-FS4TZ-T072-S	R-MS4TZ-T072+ R-FA4TZ-T072-S	R-MA4TZ-T0702+ R-FS4TZ-T072-S	R-MA4TZ-T0702+ R-FA4TZ-T072-S	U2-R4R-FS4KZ-T072-S
NPN is available, change "P" to "N" in part number					
Custom lengths and connector styles are available					
M8 connectors are available on either or both ends					

**FACTORY PRE-INSTALLED SILICONE CABLES ARE THE BEST CHOICE FOR EXTRA DURABILITY IN WELD CELLS WHERE CABLES ARE EXPOSED TO HIGH HEAT, WELD SPATTER, AND SHARP TOOLS OR PARTS.**



**HTM**  
**SENSORS**

In Canada: 3419 Mainway, Burlington, ON L7M 1A9  
 In the USA: 8651 Buffalo Ave., Niagara Falls, NY, 14304  
 Toll Free: 1-800-644-1756  
 service@htmsensors.com

Proudly Supported by

[HTMSENSORS.COM](http://HTMSENSORS.COM)