


Pneu-Turn Rotary Actuators

Pneu-Turn Actuators 4.3-4.14

Three-Position Pneu-Turn 4.15-4.17

Engineering Specifications/
Application Checklist 4.18-4.21




Bimba Pneu-Turn Rotary Actuators



TURN TO THE BIMBA PNEU-TURN® ROTARY ACTUATOR FOR THESE QUALITY FEATURES AT A LOWER COST:

The Bimba Pneu-Turn Rotary Actuator is available with these catalog options:

- Angle Adjustment
- Bumpers
- Adjustable Cushions
- Dual Shaft
- Square Key
- MRS® Magnetic Position Sensing
- Oil Service Seals
- High Temperature Option
- Ball Bearing
- Rear Shaft
- Hardened Shaft
- Anti-backlash Rack



1. **CYLINDER BODIES** – 304 stainless steel for maximum seal life.
2. **ACTUATOR BODY** – High strength, anodized aluminum alloy for maximum corrosion protection.
3. **PORTING ENDS** – High strength, anodized aluminum alloy.
4. **SHAFT** – High strength, 303 stainless steel for maximum wear resistance and long life. (hardened steel optional).
5. **SHAFT BEARINGS** – Self-lubricating, sintered iron copper material for lower friction. (ball bearings optional).
6. **PISTON SEALS** – Buna “N”, U-cup type for low breakaway friction and long life.
7. **RACK** – Carbon steel for maximum wear resistance.
8. **PINION** – High strength, alloy steel for greater durability.
9. **PISTON** – High strength, aluminum alloy.
10. **CYLINDER BODY RETAINER RING** – High strength, stainless steel for maximum corrosion protection.
11. **ANGLE ADJUSTMENT** – An option that allows 45° of adjustability each end.
12. **ADJUSTABLE CUSHIONS** – An option that controls deceleration at the end of the rotation.
13. **MRS® MAGNETIC POSITION SENSING** – An option that provides a magnet for sensing position.
14. **RACK SUPPORT** – Sintered brass material for increased load carrying capabilities.

Bimba Pneu-Turn Rotary Actuators

How to Order

The model number of Pneu-Turn Rotary Actuators consists of three alphanumeric clusters. These designate product type, series, angle of rotation and special options. Please refer to the charts below for an

example of model number PT-037090-A1DV. This is a 1-1/16" bore, single rack, 90° angle of rotation actuator with angle adjustment on both sides, dual shaft and high temperature option.

PT-037090-A1DV

SERIES – TORQUE FACTOR	
006 - 9/16" Bore, Single Rack	
014 - 9/16" Bore, Double Rack	
017 - 3/4" Bore, Single Rack	
033 - 3/4" Bore, Double Rack	
037 - 1-1/16" Bore, Single Rack	
074 - 1-1/16" Bore, Double Rack	
098 - 1-1/2" Bore, Single Rack	
196 - 1-1/2" Bore, Double Rack	
247 - 2" Bore, Single Rack	
494 - 2" Bore, Double Rack	
Single Rack see page 4.5	
Double Rack see page 4.7	
To determine theoretical output torque (in.-lbs.), place a decimal point between the first and second digits of the series number. Then multiply that number by the air line pressure for the approximate torque produced.	
For example, a PT-037-090 will produce an output torque of 0.37 times the air line pressure.	

ANGLE OF ROTATION	
045 - 45°	
090 - 90°	
180 - 180°	
270 - 270°	
360 - 360°	
Rotation angles up to 1080° are available. See page 4.18 for rotational tolerance.	

OPTIONS	
A1 - Angle adjustment (both sides)	
A2 - Angle adjustment (counterclockwise rotation)	
A3 - Angle adjustment (clockwise rotation)	
B1 - Bumpers (both sides)	
B2 - Bumper (counterclockwise rotation)	
B3 - Bumper (clockwise rotation)	
C1 - Cushions (both sides) ¹	
C2 - Cushion (counterclockwise rotation) ¹	
C3 - Cushion (clockwise rotation) ¹	
D - Dual shaft	
E - Rear shaft (front portion of dual shaft removed; to accommodate hanging axial load)	
F - Hardened shaft ²	
G - Polymer grease	
K - Square key ³	
M - Magnetic position sensing ⁴	
N - Low temperature option (-40°F) ⁸	
Q1 - Internal Flow Control (both sides) ⁹	
Q2 - Internal Flow Control (counterclockwise rotation only) ⁹	
Q3 - Internal Flow Control (clockwise rotation only) ⁹	
R - Ball bearing ²	
S - Seals – oil service ⁵	
T - Switch track ⁶	
V - High temperature option (0°F to 400°F) ⁷	
X - Anti-backlash (for 1-1/16" - 2" bores only) ⁷	

- ¹ Not available in Series 006 or 014. See below for option combination availability. See page 4.6 and 4.8 for explanation of clockwise/counterclockwise.
- ² When ordering option -F, option -R must be ordered. -R option will include dowel pin holes. Dowel pin hole locations shown in Appendix.
- ³ 006 and 014 have flat shaft.
- ⁴ Option M can be ordered with option-V, but option M's rating will change to 180°.
- ⁵ Oil service applications require 40 psi at all times or leakage will occur. 1/8 NPT ports provided (orifice omitted) for 9/16" and 3/4" bores. For double rack models, oil service seals and 1/8" ports provided on bodies A and C only.
- ⁶ Option T must be ordered in conjunction with Option M. Option M can be ordered with Option-V, but Option V's rating will change to 180°. See Position Sensing Solutions, page 8.13 for additional switch information.
- ⁷ Option X (Anti-backlash) is available in bore sizes 1-1/16", 1-1/2" and 2", single and double rack - up to 360° rotation. This option eliminates mid-rotational and end of rotation backlash in single rack models. It also eliminates mid-rotational backlash in double rack models. Double rack models do not have end of rotation backlash. All Pneu-Turns with this option include ball bearings Option R. Use this option to provide smooth rotation along with rotational precision.
- ⁸ Low temperature bumpers not available.
- ⁹ 3/4", 1-1/16", 1-1/2", 2" bore only.

Option Combination Availability

Due to design or compatibility restrictions, the following options may **not** be ordered in combination. For example, F and E options are not available in combination.

SERIES	OPTIONS													
	A	B	C	D	E	F	K	M	N	Q	R*	S	V	X
9/16" (006)	S	S	N/A	E	D,F,R,X	D,E,K			B,G,M,V	N/A	E	A,B		
9/16" (014)		S	N/A	E	D,F,R,X	D,E,K			B,G,M,V	N/A	E	B		
3/4" (017)	S	C,S	B,Q,S	E	D,F,R,X	D,E,K			B,G,M,Q,V	A,C,N,S	E	A,B,C		
3/4" (033)		C,S	B,Q,S	E	D,F,R,X	D,E,K			B,G,M,Q,V	A,C,N,S	E	B,C		
1-1/16" (037)		C,S	B,Q,S	E	D,F,R,X	D,E,K			B,G,M,Q,V	A,C,N,S	E	B,C		E,F
1-1/16" (074)		C,S	B,Q,S	E	D,F,R,X	D,E,K			B,G,M,Q,V	A,C,N,S	E	B,C		E,F
1-1/2" (098)		C,S	B,Q,S	E	D,F,R,X	D,E,K			B,G,M,Q,V	A,C,N,S	E	B,C		E,F
1-1/2" (196)		C,S	B,Q,S	E	D,F,R,X	D,E,K			B,G,M,Q,V	A,C,N,S	E	B,C		E,F
2" (247)		C,S	B,Q,S	E	D,F,R,X	D,E,K			B,G,M,Q,V	A,C,N,S	E	B,C		E,F
2" (494)		C,S	B,Q,S	E	D,F,R,X	D,E,K			B,G,M,Q,V	A,C,N,S	E	B,C		E,F

*Temperature range of ball bearing option with high temperature option is 0°F to +250°F.

Option T - "Switch track" should only be ordered with options M or V if the actuator will be operated between -20° to 85° Cj.4.9

Bimba Pneu-Turn Rotary Actuators

List Prices

Bore Size and Type	9/16"		3/4"		1-1/16"		1-1/2"		2"		
	Single (006)	Double (014)	Single (017)	Double (033)	Single (037)	Double (074)	Single (098)	Double (196)	Single (247)	Double (494)	
Base Price											
Adder per 45° Rotation											
Angle Adjustment (A1, A2, A3)											
Bumper (B1, B2, B3)											
Cushion (C1, C2, C3)											
Dual Shaft (D)											
Rear Shaft (E)											
Hardened Shaft (F)											
Square Key (K)											
MRS (M)											
Ball Bearing (R)											
Oil Service Seals (S)											
Switch Track (T)	Bore/Rotation	9/16"		3/4"		1-1/16"		1-1/2"		2"	
	45°										
	90°										
	180°										
	270°										
360°											
High Temperature Option (V) Single Rack											
High Temperature Option (V) Double Rack											
Anti-Backlash Base Option (X) ¹											
Anti-Backlash Adder per 45° Rotation (X) ²											
AV Combination											
BV Combination											
CV Combination											
SV Combination											

No charge option -G.

¹ Includes price of option-R, ball bearing option.

² Rotational adder replaces the standard adder.

Option N - List Price Adder


Bore Size	9/16"		3/4"		1-1/16"		1-1/2"		2"	
	Single (006)	Double (014)	Single (017)	Double (033)	Single (037)	Double (074)	Single (098)	Double (196)	Single (247)	Double (494)
Base Adder (N)										
Angle Adjustment - Both Sides (A1 with N)										
Angle Adjustment - One Side (A2 or A3 with N)										
Cushions - Both Sides (C1 with N)										
Cushion - One Side (C2 or C3 with N)										

Option Q - List Price Adder

Bore Size	9/16"		3/4"		1-1/16"		1-1/2"		2"	
	Single (006)	Double (014)	Single (017)	Double (033)	Single (037)	Double (074)	Single (098)	Double (196)	Single (247)	Double (494)
Internal Flow Control (Q1, Q2, Q3)										

Bimba Pneu-Turn Rotary Actuators

Single Rack Models (in.)



L1/L2 dimensions shown in chart on page 4.6.

Bore	A	B	C	E	E (With R Option)	F (C' Bores Omitted with Ball Bearing Option)	G (Std Bearing O.D. Pilot Dia.)
9/16" (006)	1.38	1.00	0.50	1.44	1.44	#8 S.H.C.S.	0.675
3/4" (017)	1.62	1.25	0.62	1.81	1.81	#10 S.H.C.S.	0.875
1-1/16" (037)	1.88	1.44	0.72	2.12	2.19	1/4" S.H.C.S.	0.968
1-1/2" (098)	2.38	1.81	0.90	2.81	2.84	5/16" S.H.C.S.	1.249
2" (247)	3.00	2.38	1.19	3.75	3.75	5/16" S.H.C.S.	1.749

Bore	G1 (Ball Bearing I.D. Pilot)	H	J	K	M	N	O	P	P1
9/16" (006)	0.750	0.250	0.61	#10-32 ¹	1.12	0.69	0.56	0.06	0.06
3/4" (017)	0.875	0.375	0.82	#10-32 ¹	1.37	1.06	0.69	0.06	0.06
1-1/16" (037)	1.125	0.500	1.12	1/8 NPT	1.75	1.31	0.88	0.06	0.09
1-1/2" (098)	1.375	0.625	1.56	1/8 NPT	2.25	1.38	1.12	0.09	0.09
2" (247)	1.875	0.875	2.08	1/4 NPT	2.56	2.00	1.28	0.11	0.10

Bore	Q	R ²	S	T	U	V	W	X
9/16" (014)	0.31	#202.5	1.03	0.61	#8-32	0.44	0.19	0.75
3/4" (033)	0.50	#204	1.25	0.73	#10-24	0.38	0.19	1.00
1-1/16" (074)	0.62	#305	1.56	0.88	1/4-20	0.50	0.25	1.25
1-1/2" (196)	0.62	#405	2.09	1.16	5/16-18	0.62	0.31	1.62
2" (494)	0.75	#606	2.56	1.28	5/16-18	0.62	0.28	2.00


¹Option-S ports are 1/8 NPT

²Key dimensions on page 4.9.

Bimba Pneu-Turn Rotary Actuators

Single Rack Options (in.)

(Dimensional variations from standard as shown.)



	9/16" (006)		3/4" (017)		1-1/16" (037)		1-1/2" (098)		2" (247)	
	L1	L2	L1	L2	L1	L2	L1	L2	L1	L2
Adder Per Degree of Rotation	0.0048	0.0048	0.0066	0.0066	0.0073	0.0073	0.0097	0.0097	0.0137	0.0137
Plus One Length Adder Below Per Side										
Base Unit (No Options)	1.52	1.52	1.63	1.63	2.03	2.03	2.34	2.34	2.84	2.84
Bumper Both Sides (B1)	1.64	1.64	1.77	1.77	2.18	2.18	2.49	2.49	3.04	3.04
Bumper CCW Side (B2)	1.52	1.64	1.63	1.77	2.03	2.18	2.34	2.49	2.84	3.04
Bumper CW Side (B3)	1.64	1.52	1.77	1.63	2.18	2.03	2.49	2.34	3.04	2.84
Cushion Both Sides (C1)	N/A	N/A	2.16	2.16	2.66	2.66	2.98	2.98	3.65	3.65
Cushion CCW Side (C2)	N/A	N/A	1.63	2.16	2.03	2.66	2.34	2.98	2.84	3.65
Cushion CW Side (C3)	N/A	N/A	2.16	1.63	2.66	2.03	2.98	2.34	3.65	2.84
Oil Service Seals (S)	1.93	1.93	2.18	2.18	2.34	2.34	2.77	2.77	3.38	3.38
Oil Service with Angle Adjustment (AS)	N/A	N/A	N/A	N/A	2.97	2.97	3.41	3.41	4.19	4.19

Note: Option A- Angle Adjustment and Option M- Magnetic Position Sensing is found on pages 4.9 and 4.10.

“CCW Side” –

refers to the extreme rotation of the shaft in the counter-clockwise direction as viewed from the mounting pilot side of the actuator.

The location of the optional feature chosen will be on tube B for single rack actuators.


“CW Side” –

refers to the extreme rotation of the shaft in the clockwise direction as viewed from the mounting pilot side of the actuator.

The location of the optional feature chosen will be on tube A for single rack actuators.

Bimba Pneu-Turn Rotary Actuators

Double Rack Models (in.)



Note: Body retainer on 2" bore has 4 corners.
L1/L2 dimensions shown in chart on page 4.8.

Bore	A	B	C	D	E	F (C' Bores Omitted with Ball Bearing Option)	G (Std Bearing O.D. Pilot Dia.)
9/16" (014)	1.38	1.00	0.50	0.83	2.06	#8 S.H.C.S.	0.675
3/4" (033)	1.62	1.25	0.62	1.04	2.50	#10 S.H.C.S.	0.875
1-1/16" (074)	1.88	1.44	0.72	1.36	3.12	1/4" S.H.C.S.	0.968
1-1/2" (196)	2.38	1.81	0.90	1.88	4.19	5/16" S.H.C.S.	1.249
2" (494)	3.00	2.38	1.19	2.56	5.13	5/16" S.H.C.S.	1.749

Bore	G1 (Ball Bearing I.D. Pilot)	H	J	K	M	N	O	P	P1
9/16" (014)	0.750	0.250	0.61	#10-32 ¹	1.12	0.69	0.56	0.06	0.06
3/4" (033)	0.875	0.375	0.82	#10-32 ¹	1.37	1.06	0.69	0.06	0.06
1-1/16" (074)	1.125	0.500	1.12	1/8 NPT	1.75	1.31	0.88	0.06	0.09
1-1/2" (196)	1.375	0.625	1.56	1/8 NPT	2.25	1.38	1.12	0.09	0.09
2" (494)	1.875	0.875	2.08	1/4 NPT	2.56	2.00	1.28	0.11	0.10

Bore	Q	R ²	S	T	U	V	W	X
9/16" (014)	0.31	#202.5	1.03	0.61	#8-32	0.44	0.19	0.75
3/4" (033)	0.50	#204	1.25	0.73	#10-24	0.38	0.19	1.00
1-1/16" (074)	0.62	#305	1.56	0.88	1/4-20	0.50	0.25	1.25
1-1/2" (196)	0.62	#405	2.09	1.16	5/16-18	0.62	0.31	1.62
2" (494)	0.75	#606	2.56	1.28	5/16-18	0.62	0.28	2.00


¹Option-S ports are 1/8 NPT (bodies "A" and "C" only).

²Key dimensions on page 4.9.

Bimba Pneu-Turn Rotary Actuators

Double Rack Options (in.)

(Dimensional variations from standard as shown.)



	9/16" (014)		3/4" (033)		1-1/16" (074)		1-1/2" (196)		2" (494)	
	L1	L2	L1	L2	L1	L2	L1	L2	L1	L2
Adder Per Degree of Rotation	0.0048	0.0048	0.0066	0.0066	0.0073	0.0073	0.0097	0.0097	0.0137	0.0137
Plus One Length Adder Below Per Side										
Base Unit (No Options)	1.52	1.57	1.63	1.68	2.03	2.08	2.34	2.39	2.84	2.89
Bumper Both Sides (B1)	1.64	1.57	1.77	1.68	2.18	2.08	2.49	2.39	3.04	2.89
Bumper CCW Side (B2)	1.64	1.57	1.77	1.68	2.18	2.08	2.49	2.39	3.04	2.89
Bumper CW Side (B3)	1.64	1.57	1.77	1.68	2.18	2.08	2.49	2.39	3.04	2.89
Cushion Both Sides (C1)	N/A	N/A	2.16	1.68	2.66	2.08	2.98	2.39	3.65	2.89
Cushion CCW Side (C2)	N/A	N/A	2.16	1.68	2.66	2.08	2.98	2.39	3.65	2.89
Cushion CW Side (C3)	N/A	N/A	2.16	1.68	2.66	2.08	2.98	2.39	3.65	2.89
Oil Service Seals (S)	1.93	1.57	2.18	1.68	2.34	2.08	2.77	2.39	3.38	2.89
Oil Service with Angle Adjustment (AS)	N/A	N/A	N/A	N/A	2.97	2.08	3.41	2.39	4.19	2.89

“CCW Side” –

refers to the extreme rotation of the shaft in the counter-clockwise direction as viewed from the mounting pilot side of the actuator.

The location of the optional feature chosen will be on tube C for double rack actuators.

“CW Side” –

refers to the extreme rotation of the shaft in the clockwise direction as viewed from the mounting pilot side of the actuator.



The location of the optional feature chosen will be on tube A for double rack actuators.

Bimba Pneu-Turn Rotary Actuators

Options

MRS® Magnetic Position Sensing


Magnetic pistons are located on the A and B tubes of both the single and double rack rotary actuators, guaranteeing switch operation at any point in the rotation.



MRS® Length Adder (in.)


Degrees	006/014	017/033	037/074	098/196	247/494
45°	0.66	0.66	0.75	0.75	0.75
90°	0.55	0.52	0.59	0.53	0.44
180°	0.34	0.22	0.26	0.09	0.00
270°	0.12	0.00	0.00	0.00	0.00
360°	0.00	0.00	0.00	0.00	0.00

Woodruff Key (in.)




Key No.	Width	Height
202.5	0.0625	0.032
204	0.0625	0.032
305	0.0938	0.047
405	0.1250	0.063
606	0.1875	0.094

Flat Key (in.) (006 and 014)



Square Key Option (in.)




Bore Size	Length	Width	Height	H
3/4" (017 / 033)	.718	.094	.094	.047
1-1/16" (037 / 074)	.797	.125	.125	.063
1-1/2" (098 / 196)	.797	.188	.188	.094
2" (247 / 494)	1.781	.25	.25	.125


Bimba Pneu-Turn Rotary Actuators

Option Dimensions (in.)


**Cushion
(C Option)**




**Angle Adjustment with
Oil Service Seals (AS Option)**



**Angle Adjustment with
Cushion (AC Option)**



**Angle Adjustment
(A Option)**



Bore	A	B	D	E	F	G	H	J
9/16" (006)	0.81	N/A	N/A	0.23	0.24	#10-32	N/A	0.53
9/16" (014)	0.81	N/A	N/A	0.23	0.24	#10-32	N/A	0.53
3/4" (017)	0.87	0.41	0.48	0.22	0.23	#10-32	N/A	0.71
3/4" (033)	0.87	0.41	0.48	0.22	0.23	#10-32	N/A	0.71
1-1/16" (037)	1.11	0.69	0.51	0.40	0.31	1/8 NPT	0.76	0.76
1-1/16" (074)	1.11	0.69	0.51	0.40	0.31	1/8 NPT	0.76	0.76
1-1/2" (098)	1.56	0.77	0.60	0.42	0.34	1/8 NPT	0.94	0.94
1-1/2" (196)	1.56	0.77	0.60	0.42	0.34	1/8 NPT	0.94	0.94
2" (247)	2.08	0.87	0.80	0.53	0.41	1/4 NPT	1.28	1.28
2" (494)	2.08	0.87	0.80	0.53	0.41	1/4 NPT	1.28	1.28

Bimba Pneu-Turn Rotary Actuators

Option N

Low Temperature Seals

Option N - Low Temperature Operation is now available as a standard catalog offering.

Pneu-Turns with seals and lubricant allowing operation to minus 40 degrees F can now be ordered directly from the catalog. Please note when ordering this option that cylinder performance may be affected beginning at temperatures below minus 20 degrees F.

Operational Note: Dry air with a dew point below the lowest temperature the actuator will experience or dry nitrogen is recommended.

Product Availability - 3 business days

Option Combination Availability

This chart provides the options that **cannot** be combined.

Due to design or compatibility restrictions, the following options may not be ordered in combination. For example, F and E options **are not** available in combination.

Option Q

Internal Flow Control


Internal flow control is now available as a standard catalog option in bore sizes 3/4", 1-1/16", 1-1/2", and 2"; both single and double rack models.

Use this option as a space saving feature and to avoid "tampering" associated with externally installed flow controls.

Flow control is achieved using a sealing disk that restricts the flow of air to the port when the piston moves towards the end cap. The restricted air is channeled through a small orifice within the end cap, on its way to the exhaust port. Controlling the flow through this orifice is achieved by adjusting a screw located on the face of the end cap. Single rack units: Clockwise (CW) and counter-clockwise (CCW) rotational flow is controlled using the end cap adjustment screw, opposite the direction of the shaft. Double rack units: CW rotation flow is adjusted using the screw in the lower end cap; CCW rotational flow is adjusted using the screw in the upper end cap. Bore sizes 3/4" and 1-1/16" provide three turns of adjustment. All larger bore sizes provide four turns of adjustment.

Option designators

- Q1 - Internal flow control (both sides)
- Q2 - Internal flow control (counter-clockwise rotation)
- Q3 - Internal flow control (clockwise rotation)



Product Availability - 3 business days

Option Q - Dimensional Variations from Standard (in.)

Single Rack	9/16" (006)		3/4" (017)		1-1/16" (037)		1-1/2" (098)		2" (247)	
	L1	L2	L1	L2	L1	L2	L1	L2	L1	L2
Adder per Degree of Rotation			0.0066	0.0066	0.0073	0.0073	0.0097	0.0097	0.0137	0.0137
Flow Control Both Sides (Q1)	N/A	N/A	2.16	2.16	2.66	2.66	2.98	2.98	3.65	3.65
Flow Control Both Sides (Q2)	N/A	N/A	1.63	2.16	2.03	2.66	2.34	2.98	2.84	3.65
Flow Control Both Sides (Q3)	N/A	N/A	2.16	1.63	2.66	2.03	2.98	2.34	3.65	2.84

Double Rack	Degree of Rotation Adder Same as Single Rack									
	9/16" (014)		3/4" (033)		1-1/16" (074)		1-1/2" (196)		2" (494)	
	L1	L2	L1	L2	L1	L2	L1	L2	L1	L2
Flow Control Both Sides (Q1)	N/A	N/A	2.16	1.68	2.66	2.08	2.98	2.39	3.65	2.89
Flow Control Both Sides (Q2)	N/A	N/A	2.16	1.68	2.66	2.08	2.98	2.39	3.65	2.89
Flow Control Both Sides (Q3)	N/A	N/A	2.16	1.68	2.66	2.08	2.98	2.39	3.65	2.89


Refer to pages 4.5-4.10 for other standard option dimensional information.

Bimba Pneu-Turn Rotary Actuators


Switch Track (T Option)

Track Locations (All other dimensions remain unchanged)


STANDARD "T" ALL BORES





ALL OTHER OPTIONS
ALL BORES EXCEPT 3/4 & 9/16



"AT" FOR 3/4 9/16 BORE




"ACT" & "CT" FOR 3/4 BORE




Bimba Pneu-Turn Rotary Actuators

Repair Parts


Standard Shaft




Ball Bearing (R) Option



Single Rack Model



Double Rack Model



Repair Parts

No.	Part Description	Quantity Required	
		Single	Double
PT-1	Actuator Body	1	1
PT-2	Shaft/Pinion Assembly	1	1
PT-3	Front Shaft Bearing	1	1
PT-4	Rear Shaft Bearing	1	1
PT-5	Shaft Key	1	1
PT-6	Piston/Rack Assembly (Includes Rack, Roll Pins and 2 Pistons)	1	2
PT-7	Rack Support	1	2
PT-8	Piston Seal ¹	2	4
PT-9	Piston Wear Ring (Required for Oil Service only)	2	2
PT-10	Magnet	2	2
PT-11	Bumper	2	2
PT-12	Bearing Retainer Set Screw	1	1
PT-13	Cylinder Body Assembly (Includes Body, End Cap, and Retainer Ring)	2	4
PT-14	Cylinder Body Retainer Cap Screw ⁴	6	12
PT-15	Cylinder Body Thread Seal	2	2
PT-16	Cylinder Body Thread Seal Ring	2	2
PT-17	Cylinder Body Jam Nut	2	2
PT-18	Angle Adjustment Screw	2	2
PT-19	Retaining Ring	2	2
PT-20	Shim Package	1	1
PT-21	Shaft Spacers ²	1	1

Repair Kits

Bearing Kit (K-A-PT) ³		
PT-3	Front Shaft Bearing	1
PT-4	Rear Shaft Bearing	1

Shaft Kit (K-S-PT)		
PT-2	Shaft/Pinion Assembly	1
PT-5	Shaft Key	1

Seal Kit (K-L-PT) ¹		
PT-8	Piston Seals	2

¹ Double Rack Models require two repair kits per rotary actuator.

Oil Service Option: Single Rack models require four oil service seals or two oil service seal kits. Double Rack models require four oil service seals and two standard seals or two oil service seal kits and one standard seal kit.

² Used on 3/4" bore single and double rack units with Ball Bearing option.

³ Bearing Kit for Ball Bearings includes retaining rings and shim package.

⁴ 2" bore requires 8 or 16.

Bimba Pneu-Turn Rotary Actuators

HOW TO ORDER

EXAMPLE: Customer needs to replace the upper piston/rack assembly on a PT-033-180-C1DM. Order is placed as:

PT - 6 - 33 - 180 - C1 - CD

A
B
C
D
E

- A. Repair Kit Part Number**
B. Series code - (Bore Size)

English	Metric
**006=06	**011=11
014=14	022=22
**017=17	**027=27
033=33	054=54
**037=37	**060=60
074=74	121=12
**098=98	**161=16
196=19	321=32
**247=24	**404=40
494=49	808=80

* Designates parts common to both Single and Double Rack Models. Use SINGLE Rack series code only.
 ** Single Rack Model.
 # Used on 3/4 inch Bore with Ball Bearing Option.

- C. Rotation** - Rotation is **only** needed in **PT-6 and PT-13**
D. Options - See Chart Below. Reference **OPTION COMBINATION AVAILABILITY CHART** in catalog for option compatibility. Options A, B and C must designate a 1, 2, or 3 (e.g. A1, B1, C1)
E. Location - For Bodies & Racks on Double Rack Models (**PT-6**, AB or CD) or (**PT-13**, A, B, C, or D)
 For Bodies on Single Rack Models (**PT-13**, A or B)

Part No.	Part Description	Options	Location
PT-1	ACTUATOR BODY	<u>only</u> possible option needed R	
* PT-2	SHAFT/PINION ASS'Y	<u>only</u> possible options needed D, E, F, K, R	
* PT-3	FRONT SHAFT BEARING	<u>only</u> possible option needed R	
* PT-4	REAR SHAFT BEARING	<u>only</u> possible option needed R	
* PT-5	SHAFT KEY	<u>only</u> possible option needed K	
PT-6	PISTON/RACK ASS'Y	<u>only</u> possible options needed B, C, M, S, X	AB or CD
* PT-7	RACK SUPPORT	<u>only</u> possible option needed X	
* PT-8	PISTON SEAL	<u>only</u> possible options needed S, V	
* PT-9	PISTON WEAR RING	no options	
* PT-10	MAGNET	no options	
* PT-11	BUMPER	<u>only</u> possible option needed V	
* PT-12	BEARING RETAINER SET SCREW	no options	
PT-13	BODY ASS'Y	<u>only</u> possible options needed A, B, C, M, S, T, V	A,B,C, or D
* PT-14	BODY RETAINER CAP SCREW	no options	
* PT-15	BODY THREAD SEAL	<u>only</u> possible option needed V	
* PT-16	BODY THREAD SEAL RING	no options	
* PT-17	BODY JAM NUT	no options	
* PT-18	ANGLE ADJ. SCREW	<u>only</u> possible options needed C, S (A if with S)	
* PT-19	RETAINING RING	no options	
* PT-20	SHIM PACKAGE	no options	
# PT-21	SHAFT SPACERS	no options	
* K-A-PT	BEARING KIT	<u>only</u> possible option needed R	
* K-L-PT	SEAL KIT	<u>only</u> possible options needed S, V	
* K-S-PT	SHAFT KIT	<u>only</u> possible options needed D, E, F, K, R	

Bimba Pneu-Turn Rotary Actuators

Three-Position Pneu-Turn




The Three-Position Pneu-Turn rotary actuators, in all bore sizes; both single and double rack can now be ordered as a standard catalog option.

How to Order

The model number for the Three-Position Pneu-Turn consists of alphanumeric characters. They designate the product; bore size, total rotation, degrees to mid-position, position of the shaft key at the mid-rotational position and options. The example below is for a 1-1/2" bore, single rack model with 225 degrees of total rotation, 45 degrees of rotation to the middle position, the key located at mid-position 8 and angle adjustment on both sides.

PT - 098225 / 045-8A1



Three-Position List Price Adders

Bore Size	9/16"		3/4"		1-1/16"		1-1/2"		2"	
	Single (006)	Double (014)	Single (017)	Double (033)	Single (037)	Double (074)	Single (098)	Double (196)	Single (247)	Double (494)
Three Position Base Adder										
**Adder per 45 degree Rotation										

**The 45-degree rotational adder shown above includes the base and three-position requirement. No additional rotational adder is required.


Option list prices are the same as the standard offering

Option Series	A	B	C	D	E	F	G	K	M	N	Q	R	S	V	X
9/16" Single	S	N,Q,S	N/A	E,F	D,F,R	D,E,K	N,S	F	N	B,G,M,V	N/A	E	A,B,G	N	N/A
9/16" Double	S	N,Q,S	N/A	E,F	D,F,R	D,E,K	N,S	F	N	B,G,M,V	N/A	E	A,B,G	N	N/A
3/4" Single	Q,S	C,N,S	B,Q,S	E,F	D,F,R	D,E,K	N,S	F	N	B,G,M,Q,V	A,C,N,S	E	A,B,C,G,Q	N	N/A
3/4" Double	Q,S	C,N,S	B,Q,S	E,F	D,F,R	D,E,K	N,S	F	N	B,G,M,Q,V	A,C,N,S	E	A,B,C,G,Q	N	N/A
1-1/16" Single	Q	C,N,S	B,Q,S	E,F	D,F,R,X	D,E,K,X	N,S	F	N	B,G,M,Q,V	A,C,N,S	E	B,C,G,Q	N	E,F
1-1/16" Double	Q	C,N,S	B,Q,S	E,F	D,F,R,X	D,E,K,X	N,S	F	N	B,G,M,Q,V	A,C,N,S	E	B,C,G,Q	N	E,F
1-1/2" Single	Q	C,N,S	B,Q,S	E,F	D,F,R,X	D,E,K,X	N,S	F	N	B,G,M,Q,V	A,C,N,S	E	B,C,G,Q	N	E,F
1-1/2" Double	Q	C,N,S	B,Q,S	E,F	D,F,R,X	D,E,K,X	N,S	F	N	B,G,M,Q,V	A,C,N,S	E	B,C,G,Q	N	E,F
2" Single	Q	C,N,S	B,Q,S	E,F	D,F,R,X	D,E,K,X	N,S	F	N	B,G,M,Q,V	A,C,N,S	E	B,C,G,Q	N	E,F
2" Double	Q	C,N,S	B,Q,S	E,F	D,F,R,X	D,E,K,X	N,S	F	N	B,G,M,Q,V	A,C,N,S	E	B,C,G,Q	N	E,F

Option T - "Switch track" should only be ordered with options M or V if the actuator will be operated between -20° to 85° C (-4° to 185° F)

Bimba Pneu-Turn Rotary Actuators

Three-Position Pneu-Turn



Single Rack Model Dimensions

	9/16" (006)				3/4" (017)				1-1/16" (037)			
	P1	P2	L1	L2	P1	P2	L1	L2	P1	P2	L1	LR
Degrees of Full Rotation Adder per degree of rotation	full rot. 0.0048	full rot. 0.0048	full rot. 0.0048	full rot. 0.0048	full rot. 0.0066	full rot. 0.0066	full rot. 0.0066	full rot. 0.0066	full rot. 0.0073	full rot. 0.0073	full rot. 0.0073	full rot. 0.0073
Degree of Stop Rotation Adder per degree of rotation	2nd stop N/A	1st stop N/A	2nd stop 0.0048	1st stop 0.0048	2nd stop N/A	1st stop N/A	2nd stop 0.0066	1st stop 0.0066	2nd stop N/A	1st stop N/A	2nd stop 0.0073	1st stop 0.0073
Base Unit (No Option)	1.41	1.41	2.82	2.82	1.63	1.63	3.05	3.05	2.03	2.03	3.89	3.89
Bumpers Both Sides (B1)	1.53	1.53	3.06	3.06	1.77	1.77	3.33	3.33	2.18	2.18	4.19	4.19
Bumper CCW Side (B2)	1.41	1.53	2.82	3.06	1.63	1.77	3.05	3.33	2.03	2.18	3.89	4.19
Bumper CW Side (B3)	1.53	1.41	3.06	2.82	1.77	1.63	3.33	3.05	2.18	2.03	4.19	3.89
Cushion/Flow Both Sides (C1) (Q1)	N/A	N/A	N/A	N/A	1.63	1.63	3.58	3.58	2.03	2.03	4.51	4.51
Cushion/Flow CCW Side (C2) (Q2)	N/A	N/A	N/A	N/A	1.63	1.63	3.05	3.58	2.03	2.03	3.89	4.51
Cushion/Flow CW Side (C3) (Q3)	N/A	N/A	N/A	N/A	1.63	1.63	3.58	3.05	2.03	2.03	4.51	3.89
Angle Adjustment Both Sides (A1)	1.41	1.41	3.05	3.05	1.63	1.63	3.27	3.27	2.03	2.30	4.28	4.28
Angle Adjustment CCW Side (A2)	1.41	1.41	2.82	3.05	1.63	1.63	3.05	3.27	2.03	2.03	3.89	4.28
Angle Adjustment CW Side (A3)	1.41	1.41	3.05	2.82	1.63	1.63	3.27	3.05	2.03	2.03	4.28	3.89

**Select Magnetic Position Sensing adder from MRS table

	1-1/2" (098)				2" (247)			
	P1	P2	L1	L2	P1	P2	L1	L2
Degrees of Full Rotation Adder per degree of rotation	full rot. 0.0097	full rot. 0.0097	full rot. 0.0097	full rot. 0.0097	full rot. 0.0137	full rot. 0.0137	full rot. 0.0137	full rot. 0.0137
Degree of Stop Rotation Adder per degree of rotation	2nd stop N/A	1st stop N/A	2nd stop 0.0097	1st stop 0.0097	2nd stop N/A	1st stop N/A	2nd stop 0.0137	1st stop 0.0137
Base Unit (No Option)	2.28	2.28	4.39	4.39	2.81	2.81	5.13	5.13
Bumpers Both Sides (B1)	2.43	2.43	4.69	4.69	3.01	3.01	5.53	5.53
Bumper CCW Side (B2)	2.28	2.43	4.39	4.69	2.81	3.01	5.13	5.53
Bumper CW Side (B3)	2.43	2.28	4.69	4.39	3.01	2.81	5.53	5.13
Cushion/Flow Both Sides (C1) (Q1)	2.28	2.28	5.03	5.03	2.81	2.81	5.95	5.95
Cushion/Flow CCW Side (C2) (Q2)	2.28	2.28	4.39	5.03	2.81	2.81	5.13	5.95
Cushion/Flow CW Side (C3) (Q3)	2.28	2.28	5.03	4.39	2.81	2.81	5.95	5.13
Angle Adjustment Both Sides (A1)	2.28	2.28	4.80	4.80	2.81	2.81	5.66	5.66
Angle Adjustment CCW Side (A2)	2.28	2.28	4.39	4.80	2.81	2.81	5.13	5.66
Angle Adjustment CW Side (A3)	2.28	2.28	4.80	4.39	2.81	2.81	5.66	5.13

**Select Magnetic Position Sensing adder from MRS table


Note:
Overall length calculator spreadsheet available. Contact the Technical Assistance Center for details.

MRS Length Adder (in.)					
Total Rotation Degrees	006/014	017/033	037/074	098/196	247/494
45°	0.66	0.66	0.75	0.75	0.75
90°	0.55	0.52	0.59	0.53	0.44
180°	0.34	0.22	0.26	0.09	0.00
270°	0.12	0.00	0.00	0.00	0.00
360°	0.00	0.00	0.00	0.00	0.00

Single rack overall width calculation: PT-098180/045-8C1--Using the chart above, calculate L1 and L2 dimensions as follows:
 $L1 = \text{Total rotation } (180) * (.0097) \text{ Full rotation adder} + \text{Degrees to 2nd stop } (135) * (.0097) \text{ 2nd stop rotation adder} + \text{Cushion adder } (5.03)$
 $L2 = \text{Total rotation } (180) * (.0097) \text{ Full rotation adder} + \text{Degrees to 1st stop } (45) * (.0097) \text{ 1st stop rotation adder} + \text{Cushion adder } (5.03)$
 $[L1 = (1.746" + 1.310" + 5.03") = 8.086"] + [L2 = (1.746" + .437 + 5.03") = 7.213"]; \text{ Total width} = 8.086" + 7.213" = 15.30"$

Bimba Pneu-Turn Rotary Actuators

Three-Position Pneu-Turn



Double Rack Model Dimensions

	9/16" (014)				3/4" (033)				1-1/16" (074)			
	P1	P2	L1	L2	P1	P2	L1	L2	P1	P2	L1	LR
Degrees of Full Rotation	full rot.	full rot.	full rot.	full rot.	full rot.	full rot.	full rot.	full rot.	full rot.	full rot.	full rot.	full rot.
Adder per degree of rotation	0.0048	0.0048	0.0048	0.0048	0.0066	0.0066	0.0066	0.0066	0.0073	0.0073	0.0073	0.0073
*Degrees to longest stop	stop rot.	stop rot.	stop rot.	stop rot.	stop rot.	stop rot.	stop rot.	stop rot.	stop rot.	stop rot.	stop rot.	stop rot.
Adder per degree of rotation	N/A	N/A	0.0048	0.0048	N/A	N/A	0.0066	0.0066	N/A	N/A	0.0073	0.0073
Base Unit (No Option)	1.41	1.46	2.82	2.87	1.63	1.68	3.05	3.10	2.03	2.08	3.89	3.94
Bumpers Both Sides (B1)	1.53	1.46	3.06	2.87	1.77	1.68	3.33	3.10	2.18	2.08	4.19	3.94
Bumper CCW Side (B2)	1.53	1.46	3.06	2.87	1.77	1.68	3.33	3.10	2.18	2.08	4.19	3.94
Bumper CW Side (B3)	1.53	1.46	3.06	2.87	1.77	1.68	3.33	3.10	2.18	2.08	4.19	3.94
Cushion/Flow Both Sides (C1) (Q1)	N/A	N/A	N/A	N/A	1.63	1.68	3.58	3.10	2.03	2.08	4.51	3.94
Cushion/Flow CCW Side (C2) (Q2)	N/A	N/A	N/A	N/A	1.63	1.68	3.58	3.10	2.03	2.08	4.51	3.94
Cushion/Flow CW Side (C3) (Q3)	N/A	N/A	N/A	N/A	1.63	1.68	3.58	3.10	2.03	2.08	4.51	3.94
Angle Adjustment Both Sides (A1)	1.41	1.46	3.05	2.87	1.63	1.68	3.27	3.10	2.03	2.08	4.28	3.94
Angle Adjustment CCW Side (A2)	1.41	1.46	3.05	2.87	1.63	1.68	3.27	3.10	2.03	2.08	4.28	3.94
Angle Adjustment CW Side (A3)	1.41	1.46	3.05	2.87	1.63	1.68	3.27	3.10	2.03	2.08	4.28	3.94

**Select Magnetic Position Sensing adder from MRS table

	1-1/2" (196)				2" (494)			
	P1	P2	L1	L2	P1	P2	L1	L2
Degrees of Full Rotation	full rot.	full rot.	full rot.	full rot.	full rot.	full rot.	full rot.	full rot.
Adder per degree of rotation	0.0097	0.0097	0.0097	0.0097	0.0137	0.0137	0.0137	0.0137
Degree of Stop Rotation	stop rot.	stop rot.	stop rot.	stop rot.	stop rot.	stop rot.	stop rot.	stop rot.
Adder per degree of rotation	N/A	N/A	0.0097	0.0097	N/A	N/A	0.0137	0.0137
Base Unit (No Option)	2.28	2.33	4.39	4.44	2.81	2.86	5.13	5.18
Bumpers Both Sides (B1)	2.43	2.33	4.69	4.44	3.01	2.86	5.53	5.18
Bumper CCW Side (B2)	2.43	2.33	4.69	4.44	3.01	2.86	5.53	5.18
Bumper CW Side (B3)	2.43	2.33	4.69	4.44	3.01	2.86	5.53	5.18
Cushion/Flow Both Sides (C1) (Q1)	2.28	2.33	5.03	4.44	2.81	2.86	5.95	5.18
Cushion/Flow CCW Side (C2) (Q2)	2.28	2.33	5.03	4.44	2.81	2.86	5.95	5.18
Cushion/Flow CW Side (C3) (Q3)	2.28	2.33	5.03	4.44	2.81	2.86	5.95	5.18
Angle Adjustment Both Sides (A1)	2.28	2.33	4.80	4.44	2.81	2.86	5.66	5.18
Angle Adjustment CCW Side (A2)	2.28	2.33	4.80	4.44	2.81	2.86	5.66	5.18
Angle Adjustment CW Side (A3)	2.28	2.33	4.80	4.44	2.81	2.86	5.66	5.18

Note:

Overall length calculator spreadsheet available. Contact the Technical Assistance Center for details.

**Select Magnetic Position Sensing adder from MRS table

Double rack overall width calculation: PT-196180/045-8C1--Using the chart above, calculate L1 and L2 dimensions as follows:
 L1 = Total rotation (180) * (.0097) Full rotation adder + Largest Degrees stop (135) * (.0097) stop rotation adder + Cushion adder (5.03")
 L2 = Total rotation (180) * (.0097) Full rotation adder + Largest Degrees stop (135) * (.0097) stop rotation adder + Cushion adder (4.44")
 [L1 = (1.746" + 1.310" + 5.03") = 8.086"] + [L2 = (1.746" + 1.310" + 4.44") = 7.496"]; Total width = 8.086" + 7.496" = 15.58"

**Notes - Largest stop rotation is used for double rack models to calculate overall L1 and L2 length. Double rack models - one body on each side will be shorter if the shaft mid-position is not 1/2 of the total rotation, the above calculation still provides the units overall width.

Bimba Pneu-Turn Rotary Actuators

Engineering Specifications

ACTUATOR OPERATION

Rotary action of the Pneu-Turn Rotary Actuator is achieved through the use of a rack and pinion assembly. Just as with a pneumatic or hydraulic cylinder, the speed of rotation may be controlled through the use of flow controls. The action at the end of the rotation can be controlled by the use of adjustable cushions, which are available as an option.

Care should be taken to insure that the inertial force does not exceed the published torque capacity. An external stop may be necessary to avoid exceeding the torque capacity due to inertial loads.

When mounting the Pneu-Turn against the shaft side of the housing, be sure to provide clearance for the pilot diameter to avoid excessive bearing pressure.

For standard models, axial loads must only be applied in the direction indicated on the dimensional drawings. The Dual Shaft or Rear Shaft options can be used to correctly orient tension induced axial loads. With the Ball Bearing option, axial loads can be applied in either direction.

The Angle Adjustment Option will allow 45° of adjustability. If cushions are ordered in conjunction with the angle adjustment option, adjustability will be 10°.

PORT POSITIONING

Ports on the Pneu-Turn may be repositioned to accommodate any air line configuration by loosening the three body retainer screws. Once desired port positions are obtained, tighten screws to specified torque values.

LUBRICATION

The Pneu-Turn Rotary Actuator is pre-lubricated at the factory for extensive, maintenance-free operation. The life of the rotary actuator can be lengthened by providing additional lubrication

with an air line mist lubricator or direct introduction of oil to the actuator every 500 hours of operation. Recommended oils for Buna N seals are medium to heavy inhibited hydraulic and general purpose oil. If High Temperature seals, use Dow Corning #710. Other types of prelube are available upon request.

The rack and pinion gear and ball bearings are prelubricated at the factory for extensive, maintenance-free operation. If additional lubrication should be required, use a high grade bearing grease.

WOODRUFF KEY LOCATION

The standard position of the woodruff key is 12 o'clock at the center of rotation.

RATINGS:

Pressure Rating: All Bimba Pneu-Turn Rotary Actuators are rated for 150 PSI air.

Rotation Tolerance: Standard rotation tolerance for 9/16" – 3/4" bore is -0° to 15° and for 1-1/16" – 2" bore is -0° to +10°.

Temperature Range: Buna N: (Standard) -20°F to +200°F; Option (V) High Temperature seals: 0°F to +400°F. Temperature range of high temperature seals with Ball Bearing option is 0°F to +250°F. If cylinders are operated at temperatures below 0° for extended time periods, special modifications may be required. Special seal materials are available on request.

Backlash:

- Without "X" option, 1-1/2° of Arc Maximum, Double rack actuators have zero backlash at end of rotational stroke
- With "X" option, single rack models have zero mid rotational and end of rotation backlash. Double rack models have zero mid-rotational backlash.

Breakaway: Less than 5 PSI.

Standard Line

Series	9/16"		3/4"		1-1/16"		1-1/2"		2"	
	(006)	(014)	(017)	(033)	(037)	(074)	(098)	(196)	(247)	(494)
Theoretical Torque Capacity (in.-lbs./PSI)	0.068	0.135	0.166	0.331	0.369	0.739	0.982	1.963	2.468	4.935
Bearing Load (Axial) (lbs.)	25	25	25	25	40	40	40	40	80	80
Bearing Load (Radial) (lbs.)	200	200	250	250	300	300	350	350	500	500
Distance Between Bearing Midpoints (in.)	0.77	0.77	0.96	0.96	1.24	1.24	1.70	1.70	1.98	1.98
Maximum Rate of Rotation (@ 100 PSI With No Load)	3000 deg./sec.	3000 deg./sec.	3500 deg./sec.	3500 deg./sec.	2000 deg./sec.	2000 deg./sec.	1500 deg./sec.	1500 deg./sec.	1000 deg./sec.	1000 deg./sec.
Weight (Approximate) (oz.)	6	11.5	11	20.5	21	38	48	89	105	152
Body Retainer Cap Screw Recommended Tightening Torque (in.-lbs.)	10	10	12	12	12	12	20	20	20	20

For Ball Bearing Option, the Following Specifications Apply

Series	9/16"		3/4"		1-1/16"		1-1/2"		2"	
	(006)	(014)	(017)	(033)	(037)	(074)	(098)	(196)	(247)	(494)
Bearing Load (Axial) (lbs.)	55	55	75	75	100	100	110	110	130	130
Bearing Load (Radial) (lbs.)	205	205	270	270	380	380	425	425	740	740
Distance Between Bearing Midpoints (in.)	.72	.72	.96	.96	1.26	1.26	1.71	1.71	1.82	1.82
Weight (Approximate) (oz.)	6	11.5	10.5	20	20.5	37.5	47	88	103	150

Bimba Pneu-Turn Rotary Actuators

Engineering Specifications

Kinetic Energy Capacity

A load connected to the shaft of a Pneu-Turn will produce kinetic energy as it is rotated. This kinetic energy must be absorbed by the Pneu-Turn or other stopping device. If the Pneu-Turn is to stop the load without external devices, then the application kinetic energy must not exceed the maximums noted in the table below.

The kinetic energy developed by your application can be determined by using the equations noted below:

$$KE = 0.5 * I * w^2$$

$$w = 1.20 * (\phi / t)$$

Maximum Allowable Kinetic Energy (in.-lbs.)

Size	Without Cushions	With Cushions
9/16" (006 / 014)	0.02	N/A
3/4" (017 / 033)	0.04	0.08
1-1/16" (037 / 074)	0.07	0.88
1-1/2" (098 / 196)	0.41	7.80
2" (247 / 494)	1.60	13.00

LEGEND:

KE = Kinetic energy (in.-lbs.)

I = Moment of inertia (in.-lb.-sec.²)

w = Rotational speed (radians/sec.)


ϕ = Angle of rotation (radians)

t = Time of rotation (sec.)

W = Weight of load (lb.)

g = Acceleration of gravity (386 in./sec.²)


Below are examples of attachments, their geometry, and the equation to use to determine the Moment of Inertia.



Thin Disc
(mounted on side
through center)

$$I = \frac{W}{g} * \frac{r^2}{4}$$


Figure 1



Thin Disc
(centered)

$$I = \frac{W}{g} * \frac{r^2}{2}$$


Figure 2



Thin Rectangular
Plate
(centered and
mounted on side)

$$I = \frac{W}{g} * \frac{(2(a1))^2}{12}$$


Figure 3



Thin Rectangular
Plate
(off-centered)

$$I = \frac{W_{a1}}{g} * \frac{4(a1)^2 + b^2}{12} + \frac{W_{a2}}{g} * \frac{4(a2)^2 + b^2}{12}$$


Figure 4



Thin Rectangular
Plate
(centered)

$$I = \frac{W}{g} * \frac{(2(a1))^2 + b^2}{12}$$


Figure 5



Slender Rod
(centered)

$$I = \frac{W}{g} * \frac{(2(a1))^2}{12}$$

Figure 6



Slender Rod
(off-centered)

$$I = \frac{W_{a1}}{g} * \frac{a1^2}{3} + \frac{W_{a2}}{g} * \frac{a2^2}{3}$$

Figure 7

Bimba Pneu-Turn Rotary Actuators

Application Possibilities


Picture the possibilities. Consider the many benefits of using the Bimba Pneu-Turn Rotary Actuator:

- Compact, Space-Saving Design
- Lightweight
- Corrosion Resistant Components
- Low Cost


Now, using the pictures on this page as a springboard, you can understand that the applications are limitless.

All you need is your imagination and a Bimba Pneu-Turn Rotary Actuator.


Transferring




Camming




Bending (Tube or Wire)




Indexing




Unloading



Opening/Closing




Turning




0° TO 360°


Clamping




Mix/Agitate




Screw/Clamping



Feeding



Valve Actuator




Bimba Pneu-Turn Rotary Actuators Checklist

Pneu-Turn Application Checklist

This checklist makes sizing and selecting Bimba actuators easier. Bimba's Engineering Department will assist you by providing a detailed analysis of your application and, based on the information in the application checklist, will help you choose the actuators best suited to your needs.

- Step 1. Photocopy the sketch and checklist sheets.**
Step 2. Complete the sketch and checklist.
Step 3. Mail or fax the sketch and checklist to your local stocking distributor.

Date: _____
 Your Name: _____
 Company: _____
 Address: _____
 Phone: _____
 Fax: _____



Request Pneu-Turn model number recommended by Engineering? Yes _____ No _____

If no, Pneu-Turn model number to be used in your application: _____

Air _____ psi Hydraulic _____ psi

Torque Required:

0 - 15 in-lbs. 75 - 100 in-lbs.
 15 - 35 in-lbs. 200 - 500 in-lbs.
 35 - 75 in-lbs. other: _____

Application closest to (circle one):

Fig. 1 Fig. 2 Fig. 3 Fig. 4 Fig. 5 Fig. 6 Fig. 7

Dimensions applicable to your lever arm:

Radius _____ in. A1 _____ in.
 A2 _____ in. B _____ in.

Weight and material of lever arm and attachments:


_____ lbs. _____ oz. material: _____

Load to be moved by the lever arm:

_____ lbs. _____ oz.

Distance from the center of the load to the center of the shaft: _____ in.

Shaft Mounted: (shaft, cylinders)



Axial loading? Yes _____ No _____

If yes, direction with reference to pushing or pulling the standard shaft: _____

Rotation of lever arm: _____ degrees

Time needed to move load in one direction:

_____ secs. Opposite direction _____ secs.

May cushions be used to slow the load at the end of stroke?

Yes _____ No _____

May external stops be used if deemed necessary?

Yes _____ No _____

Notes